

**WOOD INDUSTRIES**



**INGOTS**



**PIPE INDUSTRIES**



**STEEL**

**STEEL INDUSTRIES**



**COTTON INDUSTRIES**

**APPLICATIONS**





**CARTON SEALING MACHINE**

MODEL	PW-553S	PW-552TB	PW-555 AUC
<b>Tape Width</b>	2" or 3"	2" or 3"	2" or 3"
<b>Belt Speed</b>	20m/min (approx. 30 Cartons/min)	20m/min (approx. 30 Cartons/min)	20m/min (approx. 8 Cartons/min)
<b>Sealing Range</b>	(2") L150-∞ x W120-500 x H85-500mm(3") W+25mm	(2") L150-∞ x W200-500 x H120-500mm(3") W+25mm	(2") L300-∞ x W120-500 x H150-500mm(3") W+25mm
<b>Air Supply</b>	-	-	6Kgf/CmSq (137.64L/min)
<b>Power Supply</b>	1 Phase, 110/220/230/240V (50/60Hz) (3 Phase made on request)	1 Phase, 110/220/230/240V (50/60Hz) (3 Phase made on request)	1 Phase, 110/220/230/240V (50/60Hz) (3 Phase made on request)
<b>Machine Size</b>	L1280 x W964 x H1396 - 1761mm	L1044 x W779 x H1569 - 1764mm	L1079 x W933 x H1316 - 1576mm
<b>Operation</b>	-	-	In random or height memory function

**SEMI AUTOMATIC STRAPPING MACHINE HEAVY DUTY**



**PW-316 SL Mini**

<b>Power</b>	1Ø, 110/220V, 50 / 60Hz
<b>Strap Width</b>	9,12,15mm (Adjustable) (6mm option)
<b>Strapping: Tension</b>	15~50Kgs <b>Speed:</b> 2.0sec./Strap
<b>Strapping Size</b>	Min. : 60mm Max: Any Size
<b>Table Height</b>	330~450mm
<b>Machine Size</b>	L 1510 x W 580 x H 330mm
<b>Machine Weight</b>	85Kgs



**PW-316H**

<b>Power</b>	1Ø, 110/220V, 50 / 60Hz
<b>Strap Width</b>	9,12,15mm (Adjustable) (6mm option)
<b>Strapping: Tension</b>	15~50Kgs <b>Speed:</b> 2.0sec./Strap
<b>Strapping Size</b>	Min. : 60mm Max: Any Size
<b>Table Height</b>	750mm
<b>Machine Size</b>	L 910 x W 580 x H 750mm
<b>Machine Weight</b>	95Kgs



**PW - 0860  
 CS2B/CS2R**

<b>Power</b>	1Ø, 110/220/380/415 440V, 50/60Hz
<b>Standard Arch Size</b>	W850 x H600mm (Other Size on Request)
<b>Strapping Size (min)</b>	L 200 x W200 x H 30mm (CS2B) L 350 x W400 x H 30mm (CS2R)
<b>Strapping Width</b>	9, 12, 15mm (adjustable) (6mm option)
<b>Strapping Speed</b>	2.4sec / Strap (25 Strap / min)
<b>Table Height</b>	810mm
<b>Machine Weight</b>	L 1645 x W 760 x H 1535mm

**AUTOMATIC STRAPPING MACHINE**

**PW - 0860 AC**



<b>Power</b>	1Ø, 3Ø, 110/220/380/415/440V, 50/60Hz
<b>Standard Arch Size</b>	W850 x H600mm (Other Size on Request)
<b>Strapping Width</b>	9, 12, 15mm (adjustable) (6mm option)
<b>Strapping Speed</b>	2.4sec / Strap (25 Strap / min)
<b>Table Height</b>	810mm
<b>Machine Weight</b>	L 1510 x W 580 x H 330mm

## SEMI AUTOMATIC STRETCH WRAPPING MACHINE

**ATLANTA**  
STRETCH  
Made in Italy



MODEL	EVA	SYNTHESI	SYNTEX	MYTHO ARM, MAST
<b>Power</b>	1KW, 230 V - 1 Ph	1 KW ,230 V - 1 Ph	1 KW, 230 V - 1 Ph	1.75 KW,230 V - 1 Ph
<b>Turn Table Diameter</b>	Ø 1500 max - Std, Option (Avl)	Ø 1500 max - Std, Option (Avl)	Ø 1500 max - Std, Option (Avl)	Ø 1650 max-Std (Arm,Mast) Option (Avl)
<b>Max.Wrapping Height</b>	2200 mm	2200 mm Std, Option (Avl)	2200 mm Std, Option (Avl)	2400mm (Arm) 2500mm (Mast) Option(Avl)
<b>Max.Load Dimension &amp; Weight</b>	800x1200mm & 1500 Kg	800x1200mm & 2000 Kg	800x1200mm & 2000 Kg	1000x1200mm & 2000 Kg
<b>Adj.Turn Table Rotation Speed</b>	From 5 to 12 Rpm*	From 5 to 12 Rpm*	From 5 to 12 Rpm*	From 5 to 12 Rpm*
<b>Carriage Braking Speed</b>	FM (FTL = Force to load)	FM (FTL = Force to load)	Power Pre-Stretch One Motor (Include Gears 200%)	FM (FTL = Force to load)
<b>Up/down Spool Carriage Speed</b>	Independently Settable	Independently Settable	Independently Settable	Independently Settable
<b>Electrical Protection System</b>	IP 54	IP 54	IP 54	IP 54
<b>Adj.Spool Carriage Speed</b>	From 1,3 upto 5,4m/min	From 1,3 upto 5,4m/min	From 1,3 upto 5,4m/min	From 1,3 upto 5,4m/min
<b>Photocell Detection of Height</b>	Standard Supply	Standard Supply	Standard supply	Standard Supply
<b>Wrapping Program</b>	One Basic Program	3+1 Programs	Touch Panel with 6+1 Programs	Touch Panel with 6+1 / 99 Programs
<b>Front &amp; Rear Lifting With Fork Lift</b>	Standard Supply	Standard Supply	Standard Supply	Standard Supply
<b>Output Capacity</b>	20 Pallets Per Hour**	20 Pallets Per Hour**	20 Pallets Per Hour**	25 Pallets Per Hour**



## FULLY AUTOMATIC STRETCH WRAPPING MACHINE



MODEL	MYTHO AUTO	MYTHO STATION	LYBRA AUTO
<b>Power</b>	1 KW, 230 V - 1 Ph	2.5 KW, 400 V - 3 Ph	1.2 - 2.2(Kw), 230V - 400V - 3Ph
<b>Turn Table Diameter</b>	1800 -Std, Option (Avl)	1800 - Std	Max 1000x1200 mm
<b>Max.Wrapping Height</b>	2500 -Std, Option (Avl)	2500 - Std	2500 -Standard
<b>Max.Load Dimension &amp; Weight</b>	800x1200mm & 2000 Kg	1000 x 1200 mm &1500 Kg	1000 x 1200 mm &1500 Kg
<b>Adj.Turn Table Rotation Speed</b>	From 5 to 12 Rpm*	12 Rpm *	12 Rpm *
<b>Carriage Braking Speed</b>	FE (FTL = Magnetic brake force to load) (Included Gear 150% / 200%/250%)	FE (FTL = Magnetic brake force to load) (Included Gear 150% / 200%/250%)	-
<b>Up/down Spool Carriage Speed</b>	Independently settable	Independently Settable	-
<b>Electrical Protection System</b>	IP 54	IP 54	IP 54
<b>Adj.Spool Carriage Speed</b>	From 1,3 upto 5,4m/min	From 1,3 upto 5,4m/min	-
<b>Photocell Detection of Height</b>	Standard supply	Standard Supply	-
<b>Wrapping Program</b>	Touch Screen with 99 Programs	Touch Screen with 99 Programs	-
<b>Front &amp; Rear Lifting With Fork Lift</b>	Standard Supply	Standard Supply	-
<b>Output Capacity</b>	35 Pallets Per Hour **	35 Pallets Per Hour **	25 Pallets Per Hour **
<b>Pneumatic Pressure</b>	6 Bar	6 Bar	6 Bar
<b>STD Conveying Transport Height</b>	-	190 / 200 mm	-



**ROBOTIC STRETCH WRAPPING MACHINE**



MODEL	SFERA WITH ARM	SFERA WITH MAST	OMEGA
Power	0.55Kw, 230V - 1Ph	0.55Kw, 230V - 1Ph	8Kw, 440V - 3Ph
Turn Table Diameter	600 x 600 - Std, Option (Avl)	650 x 400 - Std, Option (Avl)	1700 - Std, Option (Avl)
Max. Wrapping Height	2000mm - Std, Option (Avl)	2200mm - Std, Option (Avl)	2000mm - Std, Option (Avl)
Max. Load Dimension & Weight	-	-	1200 x 1200mm
Adj. Turn Table Rotation Speed	Max 65 m/min	Max 65 m/min	Max 65 rpm*
Carriage Braking Speed	FE (FTL = Magnetic brake force to load) (Included Gear 150% / 200%/250%)	FE (FTL = Magnetic brake force to load) (Included Gear 150% / 200%/250%)	FE (FTL = Magnetic brake force to load) (Included Gear 150% / 200%/250%)
Up/down Spool Carriage Speed	Independently Settable	Independently Settable	Independently Settable
Electrical Protection System	IP 20	IP 20	IP 54
Adj. Spool Carriage Speed	From 1,3 upto 5,4m/min	From 1,3 upto 5,4m/min	From 1,3 upto 5,4m/min
Photocell Detection of Height	Standard Supply	Standard Supply	Standard Supply
Wrapping Program	Touch Panel with 6+1 / 99 programs	Touch Panel with 6+1 / 99 programs	Touch Panel with 7 programs
Front & Rear Lifting With Fork Lift	Standard Supply	Standard Supply	Standard Supply
Output Capacity	35 Pallets Per Hour**	35 Pallets Per Hour**	110 Pallets Per Hour**
Pneumatic Pressure	-	-	6 Bar
Conveyor Height	-	-	89 - 550mm

**PET/PP STRAPPING TOOL**



**STEEL STRAPPING TOOL**



**ACCESSORIES**



**CONSUMABLES**



**Apt Tools & Machinery India Pvt Ltd.,**

An ISO 9001:2015 Certified Company



**Head Office:** 4/226-A,  
Chinnakuyili Road, Kallapalayam Post,  
Coimbatore - 64120, Tamilnadu, India.

M : +91 80150 50510 / 97900 16774 / 96009 54151  
E : info@apttools.in / apttoolsindia@gmail.com  
W : www.aptpack.com / www.appttechnologies.in

**Chennai Branch :**  
No. 563, George Rathinam Road,  
G.G. Nagar, Nerukundram), Chennai - 600 107.  
**Product Enquiry :**  
+91 82200 14427 / 97900 16774

**Bangalore Branch :**  
No. 41, Doddanna Industrial Estate Main Rd,  
Peenya 2nd Stage, Hegganahalli, Bangalore - 560 090.  
**Product Enquiry :**  
M +91 95357 49883 / 96009 54151

**Erode Branch :**  
No 39,39/1, Neeladhari Complex,  
Kovalan Street, Erode - 638 001.  
**Product Enquiry :**  
M +91 97900-16774 /95009 54151

**Hosur Branch :**  
No 3 & 4, Vinayaka Complex  
Bangalore Road, Hosur-635 109  
**Product Enquiry :**  
M +91 77088 29009 / 96009 54151

**Coimbatore City Office :**  
No. 8, 1st Floor, Uppilipalayam Main Road,  
Sowripalayam, Coimbatore - 641 201  
**Product Enquiry :**  
M +91 96009 54151 / 97900 16774

**Hyderabad :** +91 95855 00637 / 96009 54151